

Question: 201	Which of the following are advantages of using the Modify method over dot notation?
Answer	Modification of properties in nested DataWindows is allowed.
	The control and property to be modified can be expressed programmatically
	Invalid references to DataWindow objects generate compiler versus runtime errors.
	The resulting application code runs more quickly.
Question: 202	Which of the following is not a valid metadata SaveAs type and storage format? (Choose 3)
Answer	External Schema
	External XSL
	Internal DTD
	Internal Schema
Question: 203	Which of the following classes is not a descendant of PBDOM_OBJECT?
Answer	PBDOM_ELEMENT
	PBDOM_COMMENT
	PBDOM_DOCUMENT
	PBDOM_BUILDER
Question: 204	The XSLTGen.PublishPath refers to _____
Answer	a reference to the currently associated XML template
	HTML/JS for transmission to a browser client by the web tier server
	the physical path of the Web site folder to which HTMLGenerator100 publishes the generated XSLT document.
	browser-specific JavaScript that performs the XSLT transformation on the client browser.
Question: 205	Web DataWindow controls are of the following class type when they are defined on a 4GL Web Page.
Answer	PSDataWindowSourceClass
	PSWebDataWindowClass
	HTMLGenerator100
	PSDataWindowClass
Question: 206	Set the contents of the following HTML DataWindow column property to add JavaScript to the HTML generated for a column.
Answer	ClientScriptable
	Link
	SelfLinkArguments
	ValueIsHTML
Question: 207	Which of the following are TRUE about DataWindow Object properties that control the feature set richness of generated HTML & JavaScript for a Web DataWindow? (Choose 3)
Answer	Are ignored when the DataWindow Object is used on a 4GL JSP page
	Can be set by invoking the HTMLGenerator100 component SetWeight method and passing appropriate parameters
	Have no effect on the generation characteristics of the XML Web DataWindow
	Can be set in the DataWindow Object Painter
Question: 208	Which statement best describes what it means to select the relative radio button on the generate Path in Script option of the Web DataWindow DTC?
Answer	The DataWindow Object will be included in the Web Target
	The DataWindow Object must be manually deployed to the web server
	The library in which the DataWindow Object exists is deployed with the web site
	The path to the pbl of the DataWindow Object is written into the script of the page
Question: 209	On a 4 GL DataWindow JSP page, which are server side events? (Choose 3)
Answer	AfterUpdate()
	RequestStart()

	ItemChanged()
	onload()
	AfterGenerate()
Question: 210	Which statement is TRUE regarding functions and events? (Choose 2)
	events can be posted functions cannot be posted
	The default behavior of a function is to override; the default for an event is to extend
	Functions and events can be both mapped and unmapped
Answer	Both functions and events can be made private
Question: 211	_____ is an Object Oriented Concept in which a function in a descendent object replaces a function of the same name and argument list on its ancestor object.
	Inheritance
	Abstraction
	Encapsulation
	Overloading
Answer	Overriding
Question: 212	Choose the best description of the following line of code (assume n_tr_tran is a descendant of the system class transaction): n_tr_tran = create n_tr_tran
	An instance of n_tr_tran will be created in memory, because no referenes exist for it, the object will be destroyed.
	This code will load the n_tr_tran class into the class pool, but no objects will be created in memory.
	This code will not compile, because n_tr_tran is not a valid reference variable.
Answer	The n_tr_tran object will be created and a global reference variable of the same name will automatically be declared.
Question: 213	A class that becomes instantiated is called:
	an extension class.
	an abstract class.
	a base class.
Answer	a concrete class.
Question: 214	Identify the TRUE statements with regard to external functions? (Choose 3)
	Global external functions are available anywhere in the application but can also be restricted as a part of the object's definition.
	External subroutines are the same as external functions except that they return a value.
	Local external functions must be declared before using it in script.
	Global external functions do not need to be declared before using them in script.
	Local external functions are part of the object's definition and can always be used in scripts for the object itself.
Answer	Local external functions can be made accessible to scripts other than that of the object for which it has been declared.
Question: 215	An event is defined with arguments. If it is invoked via the TriggerEvent() or PostEvent() functions
	The event will ail silently
	Attempts to access the arguments will result in a run-time error.
	The arguments are initialized to appropriate default values.
Answer	The arguments will be NULL.
Question: 216	Which of the following statements are TRUE when using the DYNAMIC keyword? (Choose 2)
	When using the DYNAMIC keyword the actual method signature is determined at execution time.
	The DYNAMIC keyword indicates that it is Strongly typed by the compiler.
	The DYNAMIC keyword applies only to methods that are associated with an object.
Answer	You can call Global functions using the DYNAMIC keyword.
Question: 217	Identify the CORRECT statements with regard to the AncestorReturnValue variable? (Choose 2)
	The AncestorReturnValue variable is generated if you extend the ancestor script and use the CALL syntax to call the ancestor event script.
	When you extend an event, the compiler automatically generates a local variable called AncestorReturnValue.
	When you extend an event, the compiler automatically generates an instance variable called AncestorReturnValue.
Answer	The AncestorReturnValue variable is generated if you override the ancestor script and use the CALL syntax to call the ancestor event script.

Question: 218	Class <code>n_utility</code> consists primarily of general utility functions and has the <code>AutoInstantiate</code> property set. A global variable of class <code>n_utility</code> , <code>gnv_utility</code> , is declared in the application. Which of the following are TRUE? (Choose 3)
	<code>gnv_utility</code> is accessible throughout the application.
	<code>n_utility</code> 's methods and properties may be accessed directly through the class.
	The statement " <code>gnv_utility = CREATE n_utility</code> " may be used to reinitialize the instance.
	If <code>n_utility</code> declares an instance variable of class <code>n_utility</code> , the object will not save.
Answer	<code>n_utility</code> represents an appropriate use of the <code>AutoInstantiate</code> property.
Question: 219	In the code shown below, what is the value of <code>lb_valid_object</code> ? <pre>powerobject lpo_object boolean lb_valid_object SetNull(lpo_object) lb_valid_object = isValid(lpo_object)</pre>
	Causes a runtime error
	Null
	True
Answer	False
Question: 220	Which event gets triggered only at the time of first expansion of an item in a Tree View?
	ItemExpanding
	ItemPopulate
	ItemCollapsing
	ItemExpanded
Answer	ItemCollapsed
Question: 221	A tab control containing one page is instantiated when a window is opened. Which of the following methods will most efficiently add tab pages with potentially different content?
	OpenUserObject
	OpenTab
	CreatePage
Answer	OpenUserObjectWithParm
Question: 222	Considering the following lines of code and assuming all references are valid, which of the statements below are TRUE? (Choose 2) <pre>Tab_1.OpenTab(u_mytabpage, 1) Tab_1.OpenTab(u_mytabpage, 1)</pre>
	The tab page becomes immediately selected
	Two tab pages are placed in the tab control
	Constructor events for controls on the tab page are immediately triggered by the system
	Only one tab page is placed in the tab control
Answer	The newly added user object references are added to the tab control's Control array
Question: 223	Which of the following have a control array? (Choose 2)
	SingleLineEdit
	Tab Control
	Menu
Answer	Window
Question: 224	Which of the following should be used for multiple selections?
	DropDownListBox
	TreeView
	MultiLineEdit
	ListBox
Answer	RadioButtons
Question: 225	Level 0 in a Treeview represents which of the following?
	Last level of items
	Root
	First level of items
Answer	An error condition

Question: 226	Compare Structures and autoinstantiated Custom Class UserObjects: Which statements are TRUE? (Choose 2)
Answer	Both are created when they are declared and destroyed when they go out of scope.
	Declaring the variable does not allocate memory for the object. After you declare it, you must instantiate it with a CREATE statement.
	Both can be inherited from an ancestor class.
Question: 227	<p>Both use dot notation to refer to properties.</p> <p>Given a Custom Class User Object n_counter , having the instance variable: private integer ii_counter And a public function: of_increment () return ii_counter ++ What will be the value of ii_counter at the end of this code segment? n_counter ln_counter ln_counter = CREATE n_counter ln_counter.ii_counter = 8 of_increment(ln_counter)</p>
Answer	10
	99
	8
Question: 228	You have the following user objects and methods defined n_foo protected string isMyName string of_hello() n_bar (inherited from n_foo) string of_goodbye() Which of the following code fragments will compile and execute correctly? (Choose 2)
Answer	n_bar myCompString sGreetingmyComp = CREATE USING "n_foo" sGreeting = myComp.DYNAMIC of_hello()
	n_foo myFooCompn_bar myBarCompmyBarComp = CREATE n_bar myFooComp = myBarCompRETURN myFooComp.DYNAMIC of_goodbye()
	n_foo myCompString sPartingMessagemyComp = CREATE USING _bar myComp.isMyName = red sPartingMessage = myComp.of_goodbye() n_bar myCompmyComp = CREATE n_bar myComp.of_hello()
Question: 229	Which of the following are methods of the SOAPConnection object? (Choose 3)
Answer	SetProxyServerOptions()
	SetMessage()
	CreateInstance()
	SetOptions()
	CreateObject()
Question: 230	When implementing a UDDI browser you use methods of the which class?
Answer	UDDIProxy
	UDDI Generator
	UDDI client
	UDDI Component
Question: 231	Which of the following is minimally mapped in a PowerDesigner Class Diagram?
Answer	Window
	User Object
	Global Function
	Structure
	DataWindow Object
Question: 232	Which libraries need to be deployed with every PowerBuilder 10 application, regardless of functionality? (Choose 3)
Answer	PBDWE100.DLL
	PBRTC100.DLL

	LIBJCC.DLL
	PBSYS100.DLL
	PBVM100.DLL
	PBSHR100.DLL
Question: 233	Which of the following DataWindow presentation styles are NOT supported with regard to accessibility support? (Choose 2)
	Composite
	Crosstab
	Graph
	Label
Answer	OLE 2.0
Question: 234	What is the default encoding format for the FileOpen() function?
	EncodingUTF8!
	EncodingANSI!
	EncodingUTF16BE!
Answer	EncodingUTF16LE!
Question: 235	You can use try-catch statements in your code if you plan to distribute your application:
	with DLLs or PBDs
	with only DLLs
	only when not using the PowerBuilder Runtime Packager
Answer	with only PBDs
Question: 236	Which of these are invalid return types from a method in an EAServer component serving as a web service? (Choose 3)
	Long
	String[]
	Any
	TabularResults
Answer	DataStore
Question: 237	The PowerDesigner plug-in allows the developer to perform which tasks? (Choose 2)
	Reverse-engineer a database to a Physical Data Model
	Generate PowerBuilder code/classes from a model
	Create a Java object-oriented model
Answer	Selectively reverse-engineer PowerBuilder classes in a specified target
Question: 238	What are the differences between user-defined object functions and user-defined global functions? (Choose 3)
	Only object functions can throw exceptions
	The access level of a global function can be changed
	User-defined global functions can be inherited
	Only object functions can be overloaded and overridden
Answer	User-defined global functions can be called from DataWindow expressions
Question: 239	What functionality does the FileReadEx method have that the FileRead method does not?
	ability to read binary files
	ability to read files specified via Unified Naming Convention (UNC)
	ability to read more than 32K bytes at a time
Answer	ability to read Unicode files in addition to ASCII files

Question: 240	<p>Assuming that the DataWindow object d_employee is in the same PBL as the object with the following script, which lines that display a message box will be executed?</p> <pre> 1 long rc 2 DataStore d 3 TRY 4 d.DataObject = "d_employee" 5 rc = d.Retrieve() 6 IF rc = -1 THEN MessageBox("Return from Retrieve", "Got Here") 7 CATCH (dwruntimeerror e1) 8 MessageBox("DWRuntimeError clause", "Got Here") 9 CATCH (runtimeerror e2) 10 MessageBox("RuntimeError clause", "Got Here") 11 CATCH (throwable e3) 12 MessageBox("Exception clause", "Got Here") 13 FINALLY 14 MessageBox("Finally clause", "Got Here") 15 END TRY </pre>
Answer	<p>Line 6 only Line 14 only Line 8 and Line 14 Line 10 and Line 14 Line 6 and Line 14</p>
Question: 241	Using the Call Stack view, you can
Answer	<p>examine an expandable list of objects currently in memory change the values of variables while debugging a remote object change the values of local variables examine the sequence of function calls leading up to the script or function that was executing at the time of the breakpoint</p>
Question: 242	Assuming the default behavior for the Transaction object, in which of the following situations will PowerBuilder commit an open transaction? (Choose 2)
Answer	<p>You issue the statement EXECUTE IMMEDIATE egin transaction before executing the database modification statements. Your application encounters an uncaught runtime error and exits. You change SQLCA.AutoCommit from true to false. You change SQLCA.AutoCommit from false to true.</p>
Question: 243	In what event might you restart or shutdown your application when there has been no user activity for a specified period of time?
Answer	<p>application's Close event MDI window's Activate event application's Idle event active window's Timer event</p>
Question: 244	Which of these tasks can be performed in both the System Tree and the Object Browser? (Choose 3)
Answer	<p>View registered ActiveX controls View the inheritance hierarchy of a set of classes View a class's defined functions View a list of global functions</p>
Question: 245	Considering the following invalid line of code, which of the statements below are TRUE? (Choose 2) dw_1.Object.DataWindow.NotReadMeOnly = 45
Answer	<p>If nested within an appropriate Try Catch block, no error handling events will occur. A DataWindow control Error event will be invoked and if the error is not handled there, the SystemError event will be invoked and the application terminated. If nested within an appropriate Try Catch block, the catch block will execute follow by a SystemError event. The SystemError event will be invoked and if the error is not handled there it will be followed by the DataWindow control Error event. A DataWindow control ItemError event will occur.</p>

Question: 246	What is the effect of the following Powerscript statement: my_app.FreeDBLibraries = TRUE
Answer	PowerBuilder libraries are held in memory after PowerBuilder disconnects from a database.
	Process initialization issues are resolved when PowerBuilder libraries are removed from memory.
	PowerBuilder libraries are released from memory after PowerBuilder disconnects from a database.
Question: 247	Event ue_sum(ref Integer a, Integer b) return (None){ a = a + 1 b = b + 2 } Function wf_show() return Integer{ Int a = 3, b = 5 Constant int c = 7 this.Event ue_sum(a, c) a = a + b + c Return a }
Answer	18
	17
	15
	16
Question: 248	After Run below power builder program what result will display? Integer i For i = 1 To 3 For i = 1 To 2 MessageBox("",i) Next Next
Answer	1 -- > 2 --> 3 --> 1 -- > 2 --> 3 --> 1 -- > 2 --> 3
	1 --> 2
	1 -- > 2 --> 1 --> 2... Result is a infinite loop.
	1 -- > 2 --> 1 -- > 2 --> 1 -- > 2
Question: 249	Which of following about the Debugger mode for Breakpoint set is correct ? Long ll_cnt -->A SELECT COUNT(*) -->B INTO :ll_cnt -->C FROM DUAL -->D USING sqlca; -->E
Answer	C,E
	D,E
	B,D
	A,B
	C,D
Question: 250	Running PowerBuilder script as below, which answer is right about ls_str? String ls_str SELECT SUBSTR('abcdcba', INSTR('abcdcba','c')) INTO ls_str FROM DUAL ;
Answer	Script is error.
	cdcba
	c
	cba
Question: 251	How to obtain dw_1 nested inside the first row, first column reports dw_ns Value.
Answer	Dw_1.getitemstring(1,dw_ns.getitemstring(1,1))
	Dw_1.Object.column[1]
	dw_1.object.dw_ns[1].object.data[1]
	Dw_1.GetItemString(1,1)
Question: 252	Which cross report the following statement is correct?
Answer	You can update only a single table
	You can update multiple tables simultaneously.
	It does not support data updates.
	With update attribute.

Question: 253	Which of the following is wrong about the PB Dynamic SQL?
	String ls_sql,ls_factnm,ls_factno ls_factno = '131' ls_sql = 'SELECT fact_nm from factm where fact_no = :A1;' EXECUTE IMMEDIATE :ls_sql INTO :ls_factnm USING :ls_factno;
	int li_id string ls_sql,ls_name,ls_filter ls_filter = '1' ls_sql="SELECT id,name FROM temp_test WHERE id>?" DECLARE c1 DYNAMIC CURSOR FOR SQLSA; PREPARE SQLSA FROM :ls_sql; OPEN DYNAMIC c1 USING :ls_filter; FETCH c1 INTO :li_id,:ls_name; DO WHILE SQLCA.SQLCODE=0 // FETCH c1 INTO :li_id,:ls_name; LOOP CLOSE c1;
	STRING ls_sql ls_sql = "INSERT INTO TABLE TEMP_TEST VALUES(1,'TTTT') EXECUTE IMMEDIATE :ls_sql;
Answer	int li_id li_id = 1 PREPARE SQLSA FROM "DELETE TEMP_TEST WHERE id=?"; EXECUTE SQLSA USING :li_id;
Question: 254	When declaring a variable (non PB keyword) in the PB code, PB will traverse the program to have the same variable name in the program, what is the traversal order of PB?
	instance variable-->local variable-->shared variable-->global variable
	global variable-->local variable-->shared variable-->instance variable
	local variable-->shared variable-->global variable-->instance variable
Answer	shared variable-->local variable-->global variable-->instance variable
Question: 255	What Functions Can DataStore Use?
	filter
	setfocus
	GetItemString
Answer	RowsCopy
Question: 256	Which are probably return values in ItemError Event?
	3
	2
	0
Answer	1
Question: 257	Which events exist in a DataStore?
	ItemChanged
	Resize
	UpdateEnd
Answer	DoubleClicked
Question: 258	Which of the following about the Status Flag for DataWindow is correct?
	Use Update Function for DataWindow, only DataModified! And NewModified! Generates SQL syntax
	When insert a row, column's status flag is New!
	When insert a row and key in data, column's status flag is DataModified!
	When data retrieve from the database, column's status flag is NotModified!
Answer	When insert a row, row's status flag is New!
Question: 259	In PowerBuilder, which Function can get data ?
	GetItemTime()
	GetItemNumber()
	GetItemDate()
	GetItemString()
Answer	GetItemLong()
Question: 260	In oracle,cursor operator including below:
	close
	execute
	open
Answer	fetch
Question: 261	Which option is not Default value of MessageBox function button parameter?
	4.YesNo!
	3.YesNoCancel!
Answer	1.OKCancel!

	2.OK!
Question: 262	<pre> STRING LS_FRONT, LS_BACK, LS_PASS, LS_PASS_2 LONG A, B, C, D, E LS_FRONT = 'JACK' LS_BACK = 'DAWSON' A = 9 B = 14 C = 72 E = (C / A) - 8 D = A * (B + C) LS_PASS = LS_FRONT + STRING(E) + LS_BACK + STRING(D) + STRING(B) LS_PASS_2 = LS_FRONT + STRING(E) + LS_BACK + STRING(A) + STRING(C) </pre> <p>IF Power Builder Syntak above is Running, what value of variable LS_PASS and LS_PASS_2 ?</p>
Answer	Syntack Error
	Error acquired
	JACK0DAWSON77414
	JACK0DAWSON972
Question: 263	Itemchanged return value argument is correct?
Answer	1 Reject the data value and do not allow focus to change
	*-1 Reject the data value and do not allow focus to change
	0 (Default) Accept the data value
	2 Reject the data value but allow the focus to change
Question: 264	Which can inherit?
Answer	User Object
	Structure
	Menu
	DataWindow Object
Question: 265	which of the following statements is wrong in Powerbuilder ?
Answer	You can delete an ancestor function from within a descendant
	Descendant can use ancestor's functions(no set private)
	when you write event scripts in a descendent object, you can extend or override scripts that have been written in the ancestor.
	when you write event scripts in a descendent object, you can cancel inheritance scripts that have been written in the ancestor.
Question: 266	Which of the following Variable equals 10?
Answer	long a = 10.3
	int a = 9.5
	double a = 10.0001
	decimal a = 10.09
	real a = 10

Question: 267	<pre>String string_now, org_string,col_ary[] Long arraylen, stringlen, place_nbr, place_tt org_string = "123,456,789" stringlen = Len(org_string) Do While stringlen > 0 place_nbr = Pos(org_string, ",") If place_nbr > 0 Then place_tt = place_nbr - 1 string_now = Mid(org_string,0,place_tt) org_string = Right(org_string,stringlen - place_nbr) stringlen = stringlen - place_nbr Else string_now = org_string org_string = Right(org_string,stringlen - place_nbr) stringlen = 0 End If arraylen = UpperBound(col_ary) col_ary[arraylen+1] = string_now Loop</pre> <p>What Is UpperBound(col_ary) Value?</p>
Answer	<p>1</p> <p>0</p> <p>null</p> <p>3</p>
Question: 268	<p>Try Catch (Throwable th) Catch (Exception ex) End Try What would happen when compiling the above code?</p>
Answer	<p>Error: Illegal data type: Throwable, Exception</p> <p>Error: Catch statement unreachable. Ancestor (or same type) is caught in previous statement.</p> <p>Error: Undefined variable: th, ex</p> <p>Compiles normally</p>
Question: 269	<p>Choose the correct answers which are valid reasons for using DataStores?</p>
Answer	<p>As part of a strategy to partition business logic from the user interface.</p> <p>To retrieve, store and manipulate data that does not need a visual representation.</p> <p>to perform multi-table updates which are not supported by the DataWindow.</p> <p>Perform database access on the user computer</p>
Question: 270	<p>What method is overloaded in PBDOM_ELEMENT ?</p>
Answer	<p>GetChildElement ()</p> <p>removeattribute ()</p> <p>removechildelement ()</p> <p>isrootelement ()</p>
Question: 271	<p>What are the join types for multi-table?</p>
Answer	<p>Cross Join</p> <p>Inner Join</p> <p>Full outer Join</p> <p>Left outer join</p>
Question: 272	<p>What are the default values for the following types?</p>
Answer	<p>Default value of Date type is 1900-01-01</p> <p>Default value of Boolean type is true</p> <p>Default value of Time type is 00:00:00</p> <p>Default value of String type is NULL</p>
Question: 273	<p>About the PB script, Which one of the following is true?</p>
Answer	<p>None of the answers</p> <p>You can write in one line as long as each block (IF block, ELSE block) contains only one Statement.</p>

	You can't write IF...ELSE statement in one line.
	You can write in one line as long as the commands in each blocks are separated by a semicolon and each block is enclosed in curly brackets.
Question: 274	Related to Menu object,Please select the correct description
	The ITEM attribute of a menu contains the menu item name
	refers to the associated menu from the Window's Activate event you use scripts 'This.MenuID'
	The ITEM attribute of a menu is an array and contains one element for each of the menu bar item
Answer	Disabling a menu item will not affect the toolbar icon
Question: 275	What is the event from which I can see the exact SQL statement that is being sent to the database by PowerBuilder?
	None of the all answer
	UpdateStart event of the DataWindow control.
	RetrieveStart event of the DataWindow control.
Answer	SQLPreview event of the DataWindow control.
Question: 276	What is the maximum characters number in PowerBuilder variables or objects identifier names?
	40
	30
	10
Answer	20
Question: 277	When the connectionbegin event of an application object is fired?
	None of the all answers
	In Both Client & Server Applications
	Server Application Only
Answer	Client Application Only
Question: 278	Relate to Menu Object , A menu item toolbar icons, which answer correct?
	You can't associate more than one toolbar icon to a menu item
	can have two toolbar icons one icon is for default display and another is when the mouse button is depressed
	can have two toolbar icons, one to display when the menu bar item is enabled, and another is when the menu bar item is disabled
Answer	can have two toolbar icons, one to display when the menu item is displayed, and another is when the menu bar item is hidden
Question: 279	Use SignalError() function in Pb Scripts will be
	Checks for any error signals
	Populates the Error object
	Fires Application SystemError event
Answer	Called from the SystemError event to indicate the error processing is about to begin
Question: 280	Which function refreshes the Datawindow automatically at a certain intervals?
	None of all the answers
	Set the DataWindow Timer property
	DataWindow.Refresh(Interval)
Answer	Return the refresh interval from the DataWindow
	What's the result of the program?
	integer i
	for i = 1 to 10
	i ++
	messagebox('values',i)
Question: 281	Next
	It's a infinite loop,No result.
	1 -> 3 -> 5 -> 7 -> 9
	1 -> 2 -> 3 -> 4 -> 5 -> 6 -> 7 -> 8 -> 9 -> 10
Answer	2 -> 4 -> 6 -> 8 -> 10

Question: 282	Which one isn't DataWindow's format?
	N-Up
	Freeform
	Grid
Answer	Matrix
Question: 283	An array is Interger c [], then LowerBound(c) will return value ?
	NULL
	-1
	0
Answer	1
Question: 284	PowerBuilder dynamic SQL, please fill in the correct script in the brackets (). string ls_Filter = "01" string ls_SQL = "SELECT code,name FROM Tab_test WHERE SUBSTR(code,3,2) = ?" string ls_Code,ls_name DECLARE cursor_base DYNAMIC CURSOR FOR SQLSA; PREPARE SQLSA FROM :ls_SQL; () FETCH cursor_base INTO:ls_Code,:ls_Name; DO WHILE SQLCA.SQLCODE=0 FETCH cursor_base INTO:ls_Code,:ls_Name; LOOP CLOSE cursor_base;
	OPEN SQLSA cursor_base USING:ls_Filter;
	OPEN DYNAMIC SQLSA cursor_base USING:ls_Filter;
	OPEN cursor_base USING:ls_Filter;
Answer	OPEN DYNAMIC cursor_base USING:ls_Filter;
Question: 285	How objects inherit after the call ue_even Ue_even ancestor object code?
	Super::ue_even()
	parent.ue_even()
	ue_even()
Answer	parent.event ue_even()
Question: 286	Which option should be used to execute a SQL statement that does not produce a result set and does not require input parameters?
	OPEN DYNAMIC my_cursor using :variable;
	PREPARE SQLSA FROM sqlstatement;
	EXECUTE SQLSA USING :variable ;
Answer	EXECUTE IMMEDIATE sqlstatement;
Question: 287	A PowerBuilder application must have an object that is?
	Menu object
	Application Object
	Window Object
Answer	DataWindow Object
Question: 288	The following syntax error that triggers the clicked event of the cb_1 button is
	cb_1.trigger event static clicked()
	cb_1.trigger event(clicked!)
	cb_1.triggerevent(clicked!)
Answer	cb_1.triggerevent("clicked")
Question: 289	Which of the following can be inherited?
	DataWindow Object
	Menu
	User Object
Answer	Structure

Question: 290	Which of the following different datawindow display types has both data maintenance and report display capabilities?
Answer	RichText
	N-UP
	Composite
	Group
Question: 291	Which answers of the array declaration is correct?
Answer	integer li_RunRate[1 to 5, 10 to 25]
	integer li_count[10 to 5]
	string ls_day[7]
	string ls_name[-10 to 15]
Question: 292	Which of the following arguments about PB function or event is on the right ().
Answer	The Reference parameters passed, its value in the function or event cannot be Modified
	The Reference parameters passed, its value can be modified in the function or Event
	The value passed parameters, its value can be modified in the function or event
	Readonly parameters passed, its value in the function or event cannot be modified
Question: 293	How to trigger the ue_event event?
Answer	This.triggerEvent("ue_event")
	This.ue_event()
	This.event ue_event()
	This.post event ue_event()
Question: 294	About powerbuilder "protect"? , which options are true?
Answer	when protect = 0 , it means column become
	when protect = 1 , it means column? become enabled
	when protect = 1 , it means column? become unenabled
	when protect = 0 , it means column become enabled
Question: 295	Which functions EXIST on the DataStore object?
Answer	SetRowFocusIndicator()
	GetItemString()
	SelectRow()
	GenerateResultSet()
Question: 296	Execute the following PB script, which the result is correct ? any la_any string ls_str la_any = 2 ls_str = la_any ls_str += 'string' messagebox("",ls_str)
Answer	runtime error
	0
	2
	2string
Question: 297	Filter() function on a non-updatable Datawindow dw_1 filtered out 12 rows out of 100 rows. Which the answer of function dw_1.FilteredCount() returns ?
Answer	NULL
	100
	0
	12
Question: 298	The following PB scripts. What return results same (a -= b+4) ? Int a , b a=0 b=10
Answer	a = a - (b+4)
	a = - (b+4)

	a = (b+4) -a
	a = 1/(b+4)
Question: 299	What all functions fire on calling update function?
Answer	UpdateStart
	UpdateEnd
	DBError
	SQLPreview
Question: 300	What are different statuses that a column can have in a DataWindow?
Answer	Clicked!
	NewModified!
	DataModified!
	NotModified!