

Question: 301	In the inheritance hirerachy, PowerBuilder is how to search ?
Answer	Just in Top
	Bottom-to-Top
	Top-to-Bottom
	Randomize
Question: 302	Which DataWindow style on Program execution , we can adjust title field to change field width ?
Answer	Group
	N-UP
	FreeForm
	Grid
Question: 303	The following PB codes import data into a datawindow with a set Group and perform Group Grouping calculations: dw_emp.ImportFile("d:\employee.txt") dw_emp.SetSort("1A") dw_emp.Sort() dw_emp._____ Which function should be used?
Answer	group()
	filter()
	groupcalc()
	SetRedraw(true)
Question: 304	After executing the following PB script , what Is J Long I,J For I = 1 To 10 Do Until I > 5 J = J + 2 If J > I Then Exit Loop Do J = J + 2 If J > I Then Exit Loop While I > 5 Next
Answer	infinite loop
	32
	16
	30
Question: 305	What is the data type of data window control's "DataObject" properties?
Answer	Enumerated
	datawindow
	string
	Any
Question: 306	Which of the following functions can be treated with a hidden field ways, but this function must be before they can perform this function in the Describe () function.
Answer	CPU()
	Evaluate()
	Run()
	GetEnvironment()
Question: 307	PowerBuilder's SQLSA,Which of the following statements is true?
Answer	You can access information in SQLSA.
	PowerBuilder provides a global DynamicStorageArea variable.
	PowerBuilder provides a global DynamicDescriptionArea variable.

	PowerBuilder provides a global DynamicStagingArea variable.
Question: 308	Which PB's variable declaration are wrong ?
	S123_%~NBA
	S123_%NBA
	123_NBA
Answer	%123_NBA
Question: 309	<p>Program code is :</p> <pre> 1 string lstr_longName , lstr_shortName 2 string Prior,Before 3 Integer l 4 Lstr_longName = lstr_shortName 5 l= 1 6 l = i++ 7 if Prior = NULL then 8 messagebox('warning','a error') 9 end if 10 lstr_longName = lstr </pre> <p>The following error statement is correct :</p>
	The seventh line, Prior = NULL , characte string can not compare with NULL
	The sixth line, l=i++ do not use an expression to the variable assignment
	Second lines, Prior reserved words can not be named for the logo
Answer	Second lines, Before reserved words can not be named for the logo
Question: 310	In PB, inheritance several categories:
	Part inheritance
	Covering inheritance
	Fully inherited
Answer	Expansion inheritance
Question: 311	Which of the following is the correct wording is dynamic SQL
	PREPARE SQLDA FROM "execute emp_select @stateparm=?" ;
	EXECUTE SQLSA USING :Dept_id_var,:Dept_name_var,:Mgr_id_var ;
	PREPARE SQLCA FROM :sqlstatement ;
	EXECUTE IMMEDIATE :MyASE USING My_trans ;
Answer	PREPARE SQLSA FROM "INSERT INTO department VALUES (?,?,:)";
Question: 312	When defining the function PASS BY parameter, you can choose which type?
	string
	reference
	readonly
Answer	value
Question: 313	In powerbuilder , which are column style types?
	CheckBox
	DropDownListBox
	RadioButton
Answer	EditMask
Question: 314	What functions do you use to change the datawindow row status?
	GetItemStatus()
	ResetUpdate ()
	SetRow()
Answer	SetItemStatus()

Question: 315	Run the following syntax to get the result that B is any a,b string c,d int e,f c='TEST' e=99 a=c+'100' a=e b=a+100
Answer	string type,result is TEST100
	string type,result is TEST99
	int type,result is 199
	int type,result is 100
Question: 316	Which of the following is printer functions?
Answer	PrintSetupPrinter
	PrintSetPrinter
	PrintGetPrinter
	PrintGetPrinters
Question: 317	Integer A, B[5,10] For A = 1 To UpperBound(B,1) A = A + 1 Next what Is A answer?
Answer	8
	7
	5
	6
Question: 318	What is the meaning of the key event parameter keyflags=1?
Answer	press Shift And Ctrl
	Not press Shift OR Ctrl
	press Shift
	press Ctrl
Question: 319	Integer li_count,i = 0,j = 5 For i = 1 To j Do li_count = li_count +1 Loop Until li_count > 5 Next MessageBox('Result',String(li_count)) What Is the result?
Answer	6
	5
	9
	10
Question: 320	The following what the value of the variables of 10?
Answer	decimal a=9.6
	double a=10.6
	long a =10.6
	int a=9.6

Question: 321	What are the Identification names in PB?
	_odd
	@mail
	This
Answer	lock \ open
Question: 322	When sharing data between two DataStore objects using the ShareData function, which information will be shared?
	Sort order
	Filter Buffer
	Primary buffer
Answer	Delete Buffer
Question: 323	Which PB scripts excute will get result '999'?
	Mid('09990',2,3)
	99' + Space (1)
	String (999,'000')
Answer	Fill('9', 3)
Question: 324	Which sequence of establishing system is correct ?
	Window-application-workspace
	workspace-application-window
	Application-window-workspace
Answer	application-workspace-window
Question: 325	PowerScript pronouns which provides correct?
	super
	parentwindow
	this
Answer	parent
Question: 326	Which can be used for time display formats
	a/p
	A/P
	AM/PM
Answer	am/pm
Question: 327	The return value of a function FileDelete () is ()
	String
	Long
	Integer
Answer	Boolean
Question: 328	Which of the following DataWindow display types can only be used for reporting?
	Tabular
	FreeForm
	Grid
Answer	CrossTab
Question: 329	How to set the column font Underline display?
	dw_1.Object.<Columnname>.Font.Underline='1'
	dw_1.Modify("<Columnname>.Font.Underline='1'")
	dw_1.Modify("<Columnname>.Font.Underline='0'")
Answer	dw_1.Object.<Columnname>.Font.Underline='0'
Question: 330	How to shield the mouse wheel?
Answer	Event other :if message.number = 525 then return 1

	Event other :if message.number = 524 then return 1
	Event other :if message.number = 522 then return 1
	Event other :if message.number = 523 then return 1
Question: 331	Run This powerscript language, Value j = ? Integer i,j j = 10 Do While i < 10 If i >= 5 Then j += i * 2 Else j -= i / 2 End If i++ Loop
Answer	20 18 74 75
Question: 332	How to set the column font bold display?
Answer	dw_1.Object.<Columnname>.Font.Weight='400' dw_1.Modify("<Columnname>.Font.Weight='400'") dw_1.Modify("<Columnname>.Font.Weight='700'") dw_1.Object.<Columnname>.Font.Weight='700'
Question: 333	How to execute the ancestor event's script from the descendant's event?
Answer	None of the above You can use ParentWindow().EVENT_NAME syntax. You can use Parent.EVENT_NAME syntax. You can use CALL SUPER::EVENT_NAME syntax
Question: 334	which options are powerbuilder standard data types?
Answer	Time UnsignedInteger Real log
Question: 335	Related to identifier names in PB scripts,which declare is wrong ?
Answer	descriptor indirected %indirect descriptors
Question: 336	What event can you trap errors in pb?
Answer	SystemError event DWRuntimeError Event DBError Event ItemError Event

Question: 337	<p>What Message appears when executing the following Syntax?</p> <pre> Any la_value Try IsValid(la_value) Catch (dvruntimeerror erdw) MessageBox('Answer', 'A') Catch (nullobjecterror er_nuo) MessageBox('Answer', 'B') Catch (runtimeerror er) MessageBox('Answer', 'C ') Finally MessageBox('Answer', 'D') End Try </pre>
Answer	A
	B
	C
	D
Question: 338	Whichever is the current target synonymous?
Answer	Parent
	ParentWindow
	This
	Super
Question: 339	In PB, Datawindow is connected to the database. What are the possible values of the returned SQLCode?
Answer	1
	-1
	100
	0
Question: 340	<p>Which line number code of the following power builder program has errors?</p> <pre> 1 integer i 2 string ls_mat_no 3 datastore lds_datastore 4 5 lds_datastore = create datastore 6 lds_datastore.dataobject = 'd_matm' 7 lds_datastore.settransobject(SQLCA) 8 lds_datastore.retrieve() 9 for i = 1 to lds_datastore.rowcount() 10 ls_mat_no = lds_datastore.getitemstring(i,'mat_no') 11 select mat_nm from matm where mat_no = :ls_mat_no ; 12 lds_datastore.setfocus() 13 lds_datastore.setitem(i,'unit','KG') 14 next </pre>
Answer	13
	12
	9
	11
Question: 341	PB. 『SQLCA.DBParm = "CommitOnDisconnect='No'"』 What does this script mean ?
Answer	Error occurs when compiling
	Rollback uncommitted data when disconnecting the database
	Commits data automatically when disconnecting the database
	Disconnect from the database
Question: 342	PB. Which the definition of below is correct for Deactivate PowerScript event ?

	Occurs just before the window becomes active.
	Occurs just after the window becomes active.
	When a window is opened, a Deactivate event occurs.
Answer	Occurs when the window becomes inactive.
Question: 343	PB. Use SetRedraw PowerScript function, Which answer of below is correct?
	dw_1.SetRedraw(1)
	dw_1.SetRedraw(0)
	dw_1.SetRedraw()
Answer	dw_1.SetRedraw(FALSE)
Question: 344	PB. OpenSheet() PowerScript function, Which the definition of below is correct?
	Opens a sheet within an MDI (multiple document interface) frame window and creates a menu item for selecting the sheet on the specified menu.
	Means open all sheet within menu item.
	Opens another sheet within a sheet window and creates a menu item for selecting the sheet on the specified menu.
Answer	Opens a main window within a sheet window and creates a menu item for selecting the main on the specified menu.
Question: 345	PB. Open() PowerScript function, Which the syntax of below is not correct?
	w_emp w_e1, w_e2 Open(w_e1) Open(w_e2)
	child lcw_data Open(w_emp, lcw_data)
	Open(w_emp)
Answer	w_emp lw_open Open(lw_open)
Question: 346	PB. Data Source in New Data Pipeline dialog box, Which the Data Source of below is not correct?
	External
	Stored Procedure
	Quick Select
Answer	Query
Question: 347	Whether the PB DataWindow dw_1 contains nested DataWindows, which syntax is right?
	dw_1.DataWindow.Object.Nested
	dw_1.DataWindow.Nested
	dw_1.Describe("DataWindow.Nested")
Answer	dw_1.Object("DataWindow.Nested")
Question: 348	in PB, opentab() function, which answer is not correct?
	Return null If any argument's value is null
	Return -1 If any argument's value is null
	Returns 1 if it succeeds
Answer	Return -1 if an error occurs
Question: 350	PB. tabcontrolname.MoveTab (source, destination) PowerScript function, Which the answer of below is correct?
	If destination is 0 or greater than the number of tabs, can not moved.
	If destination is 0 or greater than the number of tabs, the scrip be error.
Answer	If destination is 0 or greater than the number of tabs, source is moved to the end.
Question: 351	The Visible property for controls in DataWindow objects, which one is not supported?
	GroupBox
	tab
	Picture
Answer	Text
Question: 352	PB. This statement in datawindow an event script gets the type:ls_type = dwo.Type, Which Type of below ls_type value is not correct ?
	data
	report
	column
Answer	bitmap

Question: 353	PB. AcceptText method (DataWindows), Which answer of below is not correct?
	If dwcontrol is NULL, in PowerBuilder and JavaScript the method returns Error.
	When a user moves from item to item in a DataWindow control, the control validates and accepts data the user has edited.
	If dwcontrol is NULL, in PowerBuilder and JavaScript the method returns NULL
Answer	If there is no DataWindow object assigned to the DataWindow control or datastore, this method returns 1.
Question: 354	PB. Cut() PowerScript function, Which return value of below is not correct?
	-9
	1
	0
Answer	-1
Question: 355	PB. Clear() PowerScript function, Which the definition of below is correct?
	Deletes selected text or an string object from the specified control, but does not store it in the clipboard.
	Cut selected text or an OLE object from the specified control, but does not store it in the clipboard.
	Deletes selected text or an OLE object from the specified control, store it in the clipboard.
Answer	Deletes selected text or an OLE object from the specified control, but does not store it in the clipboard.
Question: 356	PB. This script, Which answer Of below Is correct? Integer li_month, li_year, ld_day1 ld_day1 = DayNumber(2000-01-01) li_month = 12 + 1 If li_month > 12 Then li_month = Mod(12, 12) li_year++ End If MessageBox("",String(li_year) + "-" +String(li_month) + "-" + String(ld_day1))
	1-0-8
	1-0-0
	0-1-0
Answer	1-0-6
Question: 357	Which winodw control's event is triggered when the window's dimension changes?
	constructor
	resize
	open
Answer	close
Question: 358	The following operators give priority to the highest?
	NOT
	*
	++
Answer	^
Question: 359	Witch one is use ShareData () need not comply with _ those conditions?
	DataWindow same number of fields
	DataWindow data the same sort
	DataWindow fields in the same order
Answer	dataWindow same field type
Question: 360	Which statement insert a row at the end of the DataWindow?
	InsertRow(0)
	Setrow(0)
Answer	Setrow(1)

	InsertRow(5)
Question: 361	The following method, which can move cursor to the specified row?
Answer	RowsMove()
	ScrollToRow()
	SelectRow()
	ScrollPriorRow()
Question: 362	If not properly save more rows of data in the data window and demanded the closure of the window, there is the system immediately triggers
Answer	Open
	Close
	CloseQuery
	DBError
Question: 363	In Powerbuilder, which is the SQLCode return value if the result of SQL execution fails ?
Answer	100
	0
	1
	-1
Question: 364	In the code dwcontrol.GetItemString(row,column,dwbuffer) , which is the dwbuffer initial value ?
Answer	Primary!
	Original!
	Delete!
	Filter!
Question: 365	Which of the following special characters are PB of tabs?
Answer	~d
	~r
	~n
	~t
Question: 366	<pre> Integer l l = 1 Do Until (l > 5) lb_1.AddItem("Hai") l = l + 1 Loop </pre> How many the result Of Loop ?
Answer	1
	6
	5
	4
Question: 367	In PB, there is a type of window that does not depend on any other window. It can be covered by other windows. It can also be covered by other windows?
Answer	Child Window
	Main Window
	Response Window
	Popup Window
Question: 368	In the datawindow, what is the only difference between views and tables () ?
Answer	View can only retrieve, add, delete data, can't modify data.
	View can only retrieve and delete data, can't add and modify data.
	View can only retrieve data, can't add,delete and modify data.
	View can only add data, can't modify data.

Question: 369	PB. Which answer Of below Is correct For Sum? Int i,j,k,Sum For i = 1 To 10 Step 5 For j = 1 To 2 For k = 1 To 2 Next Next Sum = i+j+k Next
Answer	2
	22
	11
	12
Question: 370	PB. which is the script have not error when compile?
Answer	dw_single.SetFilter("comp_no = " + gs_compno + "") dw_single.Filter(1)
	dw_single.SetFilter("comp_no = " + gs_compno + "") dw_single.Filter()
	dw_single.SetFilter("comp_no = " + gs_compno + "") dw_single.Filter("comp_no = " + gs_compno + "")
	dw_single.SetFilter("comp_no = " + gs_compno + "") dw_single.Filter(gs_compno)
Question: 371	PB. Which answer Of below Is correct? String day_name If Len(String(Today())) > 0 Then day_name = DayName(Date(Today())) MsgBox("", day_name) Else MsgBox("Error", "This date is invalid") End If
Answer	Returns the today's number.
	Returns the today's name.
	This date is invalid
	Be error when compile
Question: 372	PB. Which variable type of below is not use when create Structure?
Answer	DropDownDW
	DropDownListBox
	Datawindow
	Double
Question: 373	PB. Which the definition of below is not correct for Hide event?
Answer	Occurs just before close the another window.
	Occurs just after open the window.
	Occurs just before the window is hidden.
	Occurs just after the window is hidden.
Question: 374	PB. Which the definition of below is not correct for Reset method (Graphs in DataWindows)?
Answer	Use Reset to clear the data in a graph before you save data.
	Use Reset to clear the data in a graph after you save data.
	Use Reset to clear the data in a graph after you add new data.
	Use Reset to clear the data in a graph before you add new data.
Question: 375	PB. This script, Which answer of below is correct? SQLCA.SQLCODE = -1
Answer	Valid, non-null value
	Conversion error
	Null value
	Invalid, not null value
Question: 376	PB.This script. Which answer of below is correct? dw_1.Modify("DataWindow.QueryMode=YES")

	Modifying the WHERE clause of the DataWindow object's SQL SELECT statement
	Changing the data source of the DataWindow object on DW_1
	Remove the DataWindow's SELECT statement on DW_1
Answer	Turn on query mode so user can specify data on DW_1
Question: 377	PB. Which the definition of below is not correct for Deactivate PowerScript event ?
	Occurs just before the window becomes active.
	Occurs just after the window becomes active.
	When a window is opened, a Deactivate event occurs.
Answer	Occurs when the window becomes inactive.
Question: 378	()Style for the data window object provides a convenient way to group data
	Label
	Grid
	Group
Answer	Tabular
Question: 379	PowerScript arithmetic expression $a - = b + 4$ is equivalent to ()
	$a = - (b + 4)$
	$a = a - (b+4)$
	$a = (b + 4) - a$
Answer	$a = 1 / (b + 4)$
Question: 380	Grid in the DataWindow format is "the same amount of row data" is displayed from top down, ask what format is the data "left to right" display?
	Label
	N-UP
	Composite
Answer	Crosstab
Question: 381	Which of the following events will check the value of the Message.ReturnValue when the window is closed?
	Hide
	Deactivate
	close
Answer	Closequery
Question: 382	Run This power script,i = ? Int i For i = 20 To 40 Step 10 Do While i > 40 MessageBox(",i) Loop Next
	30
	40
	no messagebox message
Answer	50
Question: 383	Which function is used to Remove all leading and trailing white-space characters from a string ?
	trim
	left
	len
Answer	right
Question: 384	In DataWindow expression, what is the meaning of the columnname[-1]?
	Error expression
	next row columnname values.
	current row columnname values.
Answer	previous row columnname values

Question: 385	ItemChanged event, return meaning is correct?
Answer	Return 1: do not accept the input values, the focus will remain in the original field, until the correct date
	Return 2: accept input values
	Return 1: accept input values
	Return 0: do not accept the input values, but is allow turn the focus of the other fields
Question: 386	Which description is correct for DataWindow Summary's object ?
Answer	display on Last Group Page
	display on Last Page
	display on Each page
	display on Each group
Question: 387	<pre>int i i = 10.1 i = i + 0.4 MessageBox("","",i)</pre> <p>MessageBox, i display value is how much?</p>
Answer	11
	10.5
	10
	10.1
Question: 388	ID qty sum 1 10 10 2 32 42 3 11 53 4 44 97 5 55 152 Which function in computed field can return the running total?
Answer	CumulativeSum(qty for all)
	Sum(qty for all)
	Crosstabsumdec(1)
	Crosstabsum(1)
Question: 389	<p>Execute the following statement:</p> <pre>any aa = 5 string kk = "aa" aa = kk</pre> <p>Type of variable aa ?</p>
Answer	Type Uncertain
	any
	string
	int
Question: 390	PB SQL · Select col into :ls_a From tablename ; IN PB SQL statement,If not find the data, what is the value of Sqlcode?
Answer	-1
	0
	1
	100
Question: 391	<pre>Boolean lb_var1, lb_var2, lb_var3 MessageBox("", Not (lb_var1 And lb_var2)) lb_var1 = True lb_var2 = True lb_var3 = False MessageBox("", lb_var1 OR lb_var2 And lb_var3)</pre> <p>What are the first & second value of MessageBox?</p>
Answer	true, true
	false, false
	true, false
	false, true

Question: 392	To trigger button clicked event in the program, the following statement is not correct ()
Answer	cb_1.PostEvent(Clicked!)
	cb_1.trigger static event clicked()
	cb_1.triggerevent(clicked!)
	cb_1.trigger event(clicked!)
Question: 393	About the Tab Order of statements is wrong?
Answer	Max four digits
	TabOrder can be set a negative number
	When the user presses the Tab key, TabOrder will decide the order to move the focus
	TabOrder is 0 you can not keying data
Question: 394	Run This powerscript language, MessageBox will Show what Number? <pre> Long i String str str = 'A' i = 10 Choose Case Asc(str) + i Case 74 MessageBox(';1') Case 75 MessageBox(';2') Case 76 MessageBox(';3') Case Else MessageBox(';4') End Choose </pre>
Answer	4
	3
	1
	2
Question: 395	Which of the following can be the RTE control rte_1 cursor where the words are displayed separately?
Answer	rte_1.SelectTextAll()
	rte_1.SelectTextLine()
	rte_1.SelectTextWord()
	rte_1.SelectText()
Question: 396	Which can report whether the row has been modified in the datawindow?
Answer	IsRowModified()
	ModifiedCount()
	Modified()
	GetNextModified()
Question: 397	Which of the following about the window types is wrong?
Answer	CHILD type, you can not specify Menu
	MAIN type, you can open other windows under, such as Child, Popup
	POPUP type, unable to move out of range Parent window
	RESPONSE type, once opened, unless it is turned off, otherwise the system can not be applied to other functions
Question: 398	Using the SetItemStatus method(use once) to change row status ,the following statement is wrong?
Answer	NotModified! can be changed to New !
	NotModified ! can be changed to DataModified!.
	New! can be changed to NewModified!.
	DataModified! can be changed to New!.
Question: 399	Which power script , sum = 30?

	<pre> Int sum,i,j Do Do Until j > 10 j ++ sum = i + j; Loop i ++ Loop Until i > 10 MessageBox("",sum) </pre>
Answer	<pre> Int sum,i,j Do Do j ++ sum = i + j; Loop Until j > 10 i ++ Loop Until i > 10 MessageBox("",sum) </pre>
	<pre> Int sum,i,j Do Until i > 10 Do sum = i + j; j ++ Loop Until j > 10 i ++ Loop MessageBox("",sum) </pre>
	<pre> Int sum,i,j Do Until i > 10 Do Until j > 10 sum = i + j; j ++ Loop i ++ Loop MessageBox("",sum) </pre>
Question: 400	How to get the original value of Column?
Answer	<pre> getitemstring(row,column,original!) getitemstring(row,column) getitemstring(row,column,primary!,True) getitemstring(row,column,primary!,False) </pre>